

Innovative blasting to improve mining processes at Middlemount Coal

By Cesar Rosales D & B Engineer middlemount

Tapan Goswami Mining Consultant



The Middlemount project is a joint development between Peabody Energy Australia PCI Pty Ltd and Yancoal Australia Ltd.





- Middlemount Coal (MPCL) embarked on a 'process improvement' project early on this year
- Objective was to holistically approach all aspects of mining operation
- Mend each underperforming process to improve overall efficiency of the mine operation



- Very efficient and cost effective operation
- Highly motivated FIFO work force
- Produce about 5 MT of ROM and remove 60 Mbcm OB
- Mine machines:
 - EX1900, 3600, 5500, 5600,
 - D11 fleet
 - Atlas Copco drill 270/251 mm dia
 - Trucks CAT785, 789,793, EH3500 &
 - Single stage two product coal handling and preparation plant

Geometry

- Free dig prestrip, 30-35 m
- Middlemount (MM) OB, 70-90 m
- Pisces (PU) OB, 35 to 50 m
- Coal seams gently dip from 3^o to 15^o
- Fluctuations in dip & geology influence:
 - OB height
 - Stripping ratio & selective mining
- Current areas of operation





Issues



- Highwall stability
- Low machines productivity:
 - Increasing cast % and doze volume
 - Muckpile shaping & loosening
 - Excavators dig rates (pinch points)
- Cost down projects
 - Through seam and Double cast blasting
 - Combined through seam and Double cast blasting
 - Coal recovery





- Highwalls appeared to be performing reasonably well. Some barrels were clearly identifiable
- A number of blasts were scheduled to be fired through failures
- Current practice couldn't be measured & modelled
- Team agreed for reverse engineering
- Changes were made based on:
 - Sonic logs mostly competent rock
 - MIC 16t
 - Pre vs Mid-split



- Endwall split to separate blast block
- Midsplit fired S-N and multipoint initiation more favourable due to:
 - Predominantly competent rock and
 - Dip of J1 & J2 joints $80^{0}/096^{0}$ > 40^{0} to strike
- Established presence of unstable structures causing failures

Highwall stability



- Summary of design changes to minimise vibration on highwalls
 - Up to 30 holes/cluster
 - Used up to 40 ms delay
 - Endwall split
 - Unidirectional S-N
 - Multipoint initiation
- Another important change
 Top vs bottom priming



Bottom vs top priming



Bottom priming radiating energy towards highwall



Top priming radiating energy away from highwall



Acknowledgement - Dr Dane Blair, Blasting Geomechanics Pty Ltd

Highwall stability



- Measured 3 blasts fired together, lasting 20 sec
 - Used high resolution accelerometers used (0.5 Hz to 10kHz)
 - Monitored at safe location (>100 m) along the strike and behind blast



* * * * * * * * * * * *

٠ . • ١. • ۰ ٠ . ٠ . ٠ ٠ ٠ . . ٠ • • ٠ ٠ ٠ ٠ ٠ ٠ . . . ۰ ٠ ٠ ٠ ۰ . . ٠ ٠ ٠ . ٠ . . ٠ ٠ ٠ ٠ ٠ ۰ . ٠ ٠ . ۰ ٠ . ٠ . ٠ • . ٠ 0 ٠ • ٠ . ۰ ٠ . ٠ . . ð ð. ٥ ۰ . • ٠ . ۰ ۰ ٠ ٠ ٠ ٠ ٠ ٠ . . . ٠ . ۰. ٠ • . . • • • . ٠ ۰ ۰ . ٠ . ٠ ٠ . . . ۰. • . ٠ ٠ ٠ . . ٠ . • • ٠ ۰ . . • • ٠ . . ٠ ۰ .

0.8 s video time



4.1 S video time



4.6 S video time



6.5 s video time





21.9 s video time

















Vibration measurement



BLAST OUTCOME SERVICES

BOS

- Vibration acceptable but frequency require further attention 4 to 24 Hz must be avoided
- Several blasts were measured and modelled



Modelling



BLAST OUTCOME SERVICES

BOS

Measured levels and modelling proved new design is putting less energy through the highwall



New design with endsplit

Old design without endsplit



Acknowledgement - Dr Dane Blair, Blasting Geomechanics Pty Ltd

Summary of highwall stability project

- Changed practice significantly reduced vibration on the highwall
- Half barrel factor calculated to be around 90%
- Unfortunately geotechnical failures continued
- Future work:
 - Measure gas pressure at 1B (burden), 2B and 3B distances behind midsplit line
 - Dilation or contraction (positive or negative gas pressure)
 - Implement blast induced (controlled) failures around fault to make operation further safe





Uplifting machines productivity



- Wherever possible cast % was increased by:
 - Adjusting burdens
 - Front three row burdens increased
 - Rear three row burdens decreased
 - Changed over to gravel from drill cuttings after measuring VOD
 - Timing design
 - Increased between row timing
 - Decreased between spacing timing
 - Multiple point initiation
 - Achieved higher power trough



- Muckpile shaping was achieved by:
 - Closely working with schedulers dig direction agreed
 - Machines digging in the direction of firing (following timing contours) always dig better
- Multi-point initiation:
 - By combining of row-by-row, stand-up, 'V' firing, 'centre zip' within a blast
 - Cast and stand-up as required achieved
- Up to 41% cast achieved




































0.0 s video time



0.6 S video time



2.9 s video time



3.7 s video time



5.6 S video time



10.0 s video time



13.0 s video time



14.0 s video time

Multi-point initiation - example



BLAST OUTCOME SERVICES

BOS

- Use of multiple 'zip' timing
- Combined 'V', row-by-row and stand-up firing





























BLAST OUTCOME SERVICES BOS

- Mining to a RL will significantly reduce cost of operation:
 - Through-seam (TS) blasting
 - Double cast blasting
 - Combined TS & Double Cast







Cost down projects





Middlemount **BL350** Double Cast April 24, 2018

Double cast blast




















































































Cost down projects



- Double cast mixed success:
 - Only 14% cast
 - High dozer push and dig rates achieved
 - No coal damage/loss
 - High washery yield
- More work required
 - Rock property assessment
 - Displacement modelling (JK Blast model)



- Coal damage/loss (future projects)
 - Identify susceptible coal blocks where damage/loss usually occurs
 - Understand mechanism
 - Gamma log (density & natural)
 - Understand coal roof and floor
 - Manipulate stand-off distances to minimise edge loss, coal roof damage and dilution
- Ultimate aim is to maximise coal recovery per block, produce clean coal and maximise washing yield



- Significant number of projects delivered in a short five months
- Site personnel concentrate on 'keeping up with the schedule'
- In my experience site driven 'Process Improvement' projects always results savings - MCPL is a classic example where as a team worked together to deliver projects of value

Acknowledgements



- MCPL
 - Allowing me to work as part of a dynamic team and publish this work
- Action Drill & Blast
 - Accurately and painstakingly implementing D&B designs
- Dyno
 - Implementing timing designs, running simulations and supplying full proof & event free products
- Orica
- ISEE